Vehicle antenna VHF/UHF 1.3 m

PN (RN): **2036.100.34**

The antenna is designed for fixed installation on all types of wheeled and tracked vehicles. It has omnidirectional radiation pattern with vertical polarization. The antenna can be used with RF2050 transceivers in (108–146) MHz band, i.e. in the VHF II band. The antenna consists of a base and a radiator. The antenna base is equipped with a rubber cap to protect the antenna radiator thread. Inside, the antenna is designed as a centrally fed dipole, providing stable parameters independent of the counterbalance quality, which may be an issue namely in small vehicle.

Technical parameters

Frequency range	100 MHz to 512 MHz
VSWR	max. 3.5
Nominal impedance	50 Ω
Power load	max. 50 W
Gain towards	-4.5 dBi to -0.5 dBi
Antenna height	1.3 m
Maximum weight	3.65 kg
Connector	BNC (female)
Radiator length	1.05 m
Antenna base height	250 mm (including the cap)
Operating temperature	-55 °C to +71 °C
Surface finish	polyurethane lacquer
Color	olive
Standard NATO	3 or 6 screws M6 on 111 mm circle

MESIT asd, s.r.o.
Sokolovská 573, Mařatice
686 01 Uherské Hradiště
Česká republika

asd@mesit.cz
T +420 572 522 200
F
www.mesitasd.cz