PC200 - Small mains charger

Type designation: **PC200**
PN (RN): **7035.100.01**

The small mains charger charges one BP200 battery pack.

Technical parameters

Power supply voltage	mains 90 V to 264 V/ 50 Hz to 60 Hz
Current consumption	
90 V	max. 300 mA
264 V	max. 100 mA
Charging current	max. 1500 mA
Charging voltage	max. 4.25 V
Charging time	max. 8 hours
Number of connected battery packs	1
Operating temperature range during charging	0 °C to +43 °C
Termination of charging when charging current drops below	max. 125 mA
Installation dimensions	
Mains segment	W 50 mm x H 110 mm x D 81 mm
Charging position	W 27 mm x H 77 mm x D 19 mm
Weight	max. 0.3 kg

Documentation

PC200 operating instructions	7035.010.02

MESIT asd, s.r.o.
Sokolovská 573, Mařatice
686 01 Uherské Hradiště
Česká republika

asd@mesit.cz
T +420 572 522 200
F
www.mesitasd.cz

Set

Type designation	PN (RN)	Name
BP200	7040.100.01	Battery pack
PC200	7035.000.01	Small mains charger set

MESIT asd, s.r.o.
Sokolovská 573, Mařatice
686 01 Uherské Hradiště
Česká republika

asd@mesit.cz
T +420 572 522 200
F
www.mesitasd.cz