PC20 - Small mains charger

Type designation: **PC20**
PN (RN): **7046.100.11**

PC20 small mains charger charges a single LP1302, LP20 (LiIon) battery pack.

Technical parameters

Power supply voltage	mains 90 V to 264 V/ 50 Hz to 60 Hz
Current consumption	max. 0.3 A
Charging current	max. 1500 mA
Charging voltage	max. 8.5 V
Charging time	
LP1302	max. 5 hours
LP20	max. 8 hours
Number of connected battery packs	1
Operation temperature range during charging	0 °C to +43 °C
Termination of charging when charging current drops below	max. 125 mA
Installation dimensions of the charger	
Mains segment	
height	max. 110 mm
width	max. 50 mm
depth	max. 81 mm
Charging position	
height	max. 75 mm
width	max. 43 mm
depth	max. 68 mm
Charger weight	max. 0.28 kg

MESIT asd, s.r.o.
Sokolovská 573, Mařatice
686 01 Uherské Hradiště
Česká republika

asd@mesit.cz
T +420 572 522 200
F
www.mesitasd.cz

Documentation

PC20 operating instructions	7046.010.12

Set

Type designation	PN (RN)	Name
PC20	7046.000.12	Small mains charger set

Battery packs

Type designation	PN (RN)	Name
LP1302	7029.100.02	Battery pack
LP20	7029.100.11, 7029.100.13	Battery pack

MESIT asd, s.r.o.
Sokolovská 573, Mařatice
686 01 Uherské Hradiště
Česká republika

asd@mesit.cz
T +420 572 522 200
F
www.mesitasd.cz