NK13 - Trickle charger

Type designation: **NK13**
NSN: **6130160037999**
PN (RN): **7002.100.02**
KČN: **0299012010862**

The charger is used for elimination of self-discharging of NiCd battery packs RF13.1 during storage. Charged battery packs are stored close to the trickle charger. They are interconnected with a cable (7002.900.01). One trickle charger can charge up to 30 battery packs at the same time.

Technical parameters

Power supply voltage	mains 230 V/50 Hz
Charging time	unlimited
Trickle current	30 mA
Charging control	constant charging current
Protection provided by enclosure	IP 30
Operating temperature range	-20 °C to +50 °C
Dimensions	W 340 mm x H 95 mm x D 255 mm
Weight	4 kg

Documentation

NK13 operating instructions	7002.010.02

Set

Type designation	PN (RN)	Name
NK13	7002.000.02	Trickle charger set

MESIT asd, s.r.o.
Sokolovská 573, Mařatice
686 01 Uherské Hradiště
Česká republika

asd@mesit.cz
T +420 572 522 200
F
www.mesitasd.cz

Batteries

Type designation	PN (RN)	Name
RF13.1	7000.000.02	Rechargeable battery pack set

MESIT asd, s.r.o.
Sokolovská 573, Mařatice
686 01 Uherské Hradiště
Česká republika

asd@mesit.cz
T +420 572 522 200
F
www.mesitasd.cz