GPA24 - Satellite navigation antenna (with choke ring)

Type designation: **GPA24**
NSN: **5985160020273**
PN (RN): **2042.100.80**
KČN: **0064681101281**

This antenna can be installed in fixed locations. Antenna consists of a GPA24 satellite navigation antenna and a choke ring. Choke ring provides to GPA24 antenna high immunity to both RFI and multipath effects especially in the undulated terrain.

Technické parametry

Zářič	mikropáskový s kruhovou pravotočivou polarizací
Jmenovitý kmitočet	1575,42 MHz
Jmenovitá impedance	50 Ω
Maximální PSV na výstupu	3
Napájecí napětí	3,3 V až 12 V
Výstupní konektor	BNC
Rozsah pracovních teplot	-30 °C až +60 °C
Rozměry GPA24 (2042.100.80)	prům. 362 mm x 134 mm
Hmotnost GPA24 (2042.100.80)	3 kg
Rozměry GPA24 (2042.100.85)	prům. 435 mm x 505 mm
Hmotnost GPA24 (2042.100.85)	4 kg

MESIT asd, s.r.o.
Sokolovská 573, Mařatice
686 01 Uherské Hradiště
Česká republika

asd@mesit.cz
T +420 572 522 200
F
www.mesitasd.cz

Průvodní dokumentace

Návod k obsluze GPA24, GPA25	2042.010.01
Záznamník	6000002011
Technický list	6000002021

Set

Type designation	PN (RN)	Name
GPA24	2042.000.80	Satellite navigation antenna (with choke ring) set

MESIT asd, s.r.o.
Sokolovská 573, Mařatice
686 01 Uherské Hradiště
Česká republika

asd@mesit.cz
T +420 572 522 200
F
www.mesitasd.cz