

NM13 - Mobile charger

Type designation: **NM13**

NSN: **6130160038293**

PN (RN): **7004.100.01**

KČN: **0068600200062**

The charger is used for charging of the single battery pack RF13.1 by a constant current. This charger makes possible the charging of the battery pack at mobile sets by means of an on-board mains of 12 V or 24 V. Temperature increase of the battery pack above +43 °C causes the standard charging current switch-off and consequently the trickle charge mode is switched on. The chargers can be fixed to horizontal or vertical surfaces with four M4 screws. They are connected to the on-board mains by means of a power cable with a cigarette lighter adapter, which is included with the charger. The battery pack is fastened to the charger with a lever closure. The charging stops automatically.

Technické parametry

Rozsah napájecích napětí	10 V až 33 V
Nabíjecí proud	400 mA
Doba nabíjení	(14 až 16) hodin
Konzervační proud	(30 ± 15) mA
Rozsah pracovních teplot	-20 °C až +50 °C
Rozsah teplot při nabíjení	-20 °C až +40 °C
Rozměry [š x v x h]	192 mm x 68 mm x 81 mm
Hmotnost	max. 1 kg

Průvodní dokumentace

Návod k obsluze NM13	7004.010.01
Záznamník	6000002011
Technický list	6000002021

Set

Type designation	PN (RN)	Name
------------------	---------	------

NM13	7004.000.01	Mobile charger
------	-------------	----------------

Batteries

Type designation	PN (RN)	Name
------------------	---------	------

RF13.1	7000.000.01	Rechargeable battery pack set
--------	-------------	-------------------------------