LP40 - Battery

Type designation: **LP40**
PN (RN): **7400.100.01, 7400.100.02, 7400.100.03, 7400.100.04**

LP40 battery is offered in two versions. Optimal battery type choice for a given application depends on the required radio operating time, dimensions and weight.

Battery design:
• LP40L battery with a capacity of 82 Wh (7400.100.01)
• LP40L battery with a capacity of 96 Wh (7400.100.03) - not suitable for low temperature conditions

• LP40S battery with a capacity of 41 Wh (7400.100.02)
• LP40S battery with a capacity of 48 Wh (7400.100.04) - not suitable for low temperature conditions

Provozní možnosti

• kompaktní mechanická konstrukce s kontaktním systémem zabezpečujícím snadné a spolehlivé mechanické spojení s radiostanicí nebo nabíječem,
• kontaktní systém s komunikačním rozhraním pro přenos základních údajů do radiostanice (aktuální stav nabití) a údajů pro řízení nabíjecího režimu,
• LCD zobrazovač s indikátorem stavu nabití formou bargrafu,
• sekundární pár kontaktů pro dobíjení baterie v dobíjecím stojánku za provozu radiostanice.

Chargers

Type designation	PN (RN)	Name
SC40	7410.100.01	Stationary charger
PC40	7411.100.01	Simple charger
VC40	7412.100.01	Vehicle charger
SL40	7047.100.40	Solar charger

MESIT asd, s.r.o.
Sokolovská 573, Mařatice
686 01 Uherské Hradiště
Česká republika

asd@mesit.cz
T +420 572 522 200
F
www.mesitasd.cz