MA1302 - Vehicle support

Type designation: **MA1302**

PN (RN): **7018.100.21**

MA1302 vehicle support supplies RF20 transceivers with power and charges battery packs for this transceiver in vehicles with 12 V or 27 V board mains (compatible with MIL-STD-1275B). When removed with the battery pack from the holder, the transceiver becomes portable and capable of normal operation.

Technické parametry

Napájecí napětí z palubní sítě vozidla	12 V nebo 27 V
Rozsah napájecího napětí	10 V až 33 V
Odběr proudu z palubní sítě vozidla	max. 4 A
Odběr proudu v pohotovostním režimu	max. 3 mA
Výstupní napětí	max. 9 V
Napájecí proud do radiostanice	min. 3,5 A
Nabíjecí proud BP1301	150 mA
Nabíjecí proud LP1302, LP20	max. 1,8 A
Nabíjecí napětí pro BP1301	max. 9 V
Nabíjecí napětí pro LP1302	max. 8,4 V
Rozsah teploty zdrojové skříně pro nabíjení	0 °C až 43 °C
Rozsah pracovních teplot	-40 °C až +70 °C
Rozměry [š x v x h]	215 mm x 200 mm x 60 mm
Hmotnost	max. 1 kg

Průvodní dokumentace

Návod k obsluze MA1302	7018.010.21
Záznamník	6000002011

MESIT asd, s.r.o.
Sokolovská 573, Mařatice
686 01 Uherské Hradiště
Česká republika

asd@mesit.cz
T +420 572 522 200
F
www.mesitasd.cz

Set

Type designation	PN (RN)	Name
MA1302	7018.000.25	Vehicle support set

Battery packs

Type designation	PN (RN)	Name
LP1302	7029.100.02	Battery pack
LP20	7029.100.11, 7029.100.13	Battery pack

MESIT asd, s.r.o.
Sokolovská 573, Mařatice
686 01 Uherské Hradiště
Česká republika

asd@mesit.cz
T +420 572 522 200
F
www.mesitasd.cz