NS13 - Standard battery charger

Type designation: **NS13**
NSN: **6130160037710**
PN (RN): **7003.100.01**
KČN: **0299012010800**

The charger is used for simultaneous charging of one to six rechargeable battery packs RF13.1 at 0.1 C standard current. Temperature increase of the battery pack above +43 °C causes the standard charging current switch-off and consequently the trickle charge mode is switched on. Charged battery packs are fastened to the charger by means of level closures. The charger can be carried with the charged battery packs.

Technické parametry

Napájecí napětí	síťové 230 V/50 Hz
Doba nabíjení	(14 až 16) hodin
Nabíjecí proud	400 mA
Konzervační proud	30 mA
Krytí	IP 30
Rozsah prac. teplot	-20 °C až +50 °C
Rozměry [š x v x h]	225 mm x 250 mm x 315 mm
Hmotnost	5,5 kg

Průvodní dokumentace

Návod k obsluze NS13	7003.010.01
Záznamník	6000002011
Technický list	6000002021

MESIT asd, s.r.o.
Sokolovská 573, Mařatice
686 01 Uherské Hradiště
Česká republika

asd@mesit.cz
T +420 572 522 200
F
www.mesitasd.cz

Set

Type designation	PN (RN)	Name
NS13	7003.000.01	Standard battery charger set

Battery packs

Type designation	PN (RN)	Name
RF13.1	7000.000.01	Rechargeable battery pack set

MESIT asd, s.r.o.
Sokolovská 573, Mařatice
686 01 Uherské Hradiště
Česká republika

asd@mesit.cz
T +420 572 522 200
F
www.mesitasd.cz