Headset

PN (RN): **2328.100.11, 2328.100.12**

Light-weight headband headset consists of a central housing unit supporting a microphone and earphone, are mounted on flexible boom arms which can be rotated and instantly configured to accommodates both left side or right side users. The headset can be connected to RF23 or RF2350 transceivers with U-229/U type connector.

Headset 2328.100.11 includes the extra PTT key with velcro to fix on hand or weapon.

Provozní možnosti

- dynamický mikrofon s potlačením okolního hluku,
- vodotěsné provedení IP67,
- splňuje požadavky MIL-STD,
- velké klíčovací tlačítko,
- upevnění pomocí čelenkového popruhu.

Technické parametry

SPECIFIKACE REPRODUKTORU	
Typ reproduktoru	magnetodynamický
Impedance	300 Ω ± 15 %
Kmitočtový rozsah	200 Hz až 4000 Hz
Citlivost	85 ± 3 dB/mW na 1 kHz
Výkonové zatížení	20 mW
Maximální výkonové zatížení	100 mW
SPECIFIKACE MIKROFONU	
Typ mikrofonu	magnetodynamický
Impedance	max. 150 Ω na 1 kHz
Kmitočtový rozsah	200 Hz až 4000 Hz
Rozsah provozních teplot	-55 °C až +70 °C
Vlhkost	96 %
Atmosferický tlak	86 kPa–106 kPa

MESIT asd, s.r.o.
Sokolovská 573, Mařatice
686 01 Uherské Hradiště
Česká republika

asd@mesit.cz
T +420 572 522 200
F
www.mesitasd.cz